MINI2



Designed to boost productivity and speed, with extra-bright screen, long-lasting battery, and improved GPS technology to perform better in natural surroundings

- 800x480 WVGA LCD TFT display
- Fast 1.0 GHz processor
- Scratch-resistant, touch-screen display, highly readable in both low light and glaring sunshine
- 3.6"w x 7.25"h x 1.5" deep
- Weighs just 1.3 lbs
- Dustproof and waterproof rating of IP68
- Meets MIL-STD-810G standard
- Options include an integrated 3G modem,
 5 mega-pixel camera, or GPS/GNSS module

The Carlson MINI2 comes with either Carlson SurvCE, the world's most popular data collection software...

...or, for accident and crime reconstruction, **Carlson CSI Mobile**





The Carlson MINI2 is built for the field. It is waterproof and dustproof (IP68) featuring long battery life, sunlight readable display, and operation under extreme temperatures.

PROCESSOR

 1.0GHz ARM Cortex A8 i.MX53 processor

OPERATING SYSTEM AND SOFTWARE

- Microsoft® Windows Embedded Handheld 6.5.3
- Microsoft Office Mobile 2010* (Word Mobile, Excel Mobile, PowerPoint Mobile, Outlook Mobile)
- Multiple languages (English, French, Spanish, German, Portuguese)

MEMORY AND DATA STORAGE

- 512MB RAM
- 8GB flash storage
- User-accessible micro SD/SDHC slot

DISPLAY

- Active viewing area: 4.3" (109 mm) WVGA LCD TFT (800x480)
- High visibility backlit LCD
- Portrait or landscape orientation

TOUCH SCREEN

- Projected capacitive touch interface "optically bonded" to display for increased visibility
- Chemically-strengthened glass

KEYBOARD

- Adjustable LED backlit keys
- Five-way directional navpad
- Numeric keypad (6 user reassignable)
- OEM configurable/customizable

PORTS

- COM1, RS-232C 9-pin D connector with 5VDC power output
- USB host (Full A), USB client (Micro B)
- 12, 24VDC @ 1.5-3.5A, 10-36V unregulated
- 3.5 mm audio jack, supports speaker/ microphone or stereo output (pin detect)
- I/O module OEM configurable/ customizable

BATTERY

 Intelligent Li-Ion battery 3.7VDC @ 10600mAh, 38.7Whr

- Operates for up to 20 hours on one charge
- Charges in 2 to 4 hours
- Battery easily changeable in field
- Optimized for excellent performance in cold temperatures

PHYSICAL

- Size, Standard models: 3.6"w x
 7.25"lx1.5"d (91 x184 x 38 mm)
- Weight: 1.3 lbs (590 g)
- Durable hardened plastic in a shear-proof and shock-resistant design
- Strong chemical resistance
- Comfortable, wide hand strap
- Easy-to-grip, impact-absorbing bumpers

EXTREME ENVIRONMENTAL CONDITIONS

- IP68 waterproof and dustproof
- Operating temperature:
 -22F to 131F (-30C to 55C)
- Storage temperature:

 -22F to 158F (-30C to 70C)

 Note: Bluetooth® wireless technology is rated to -4F (-20C)
- Shockproof: multiple drops from 4'-5' (1.2-1.5 m) onto concrete
- MIL-STD-810G test procedures: Method 500.5 Low Pressure (Altitude);

Method 501.5 High
Temperature; Method 502.5
Low Temperature; Method 503.5
Temperature Shock; Method
506.5 Rain;

Method 507.5 Humidity; Method 510.5 Sand and Dust; Method 512.5 Immersion; Method 514.6 Vibration; Method 516.6 Shock

WIRELESS CONNECTIVITY OPTIONS

- Bluetooth® wireless technology, 2.1 +EDR, Class 1.5, range 100 feet (30 m)
- Wi-Fi 802.11b/g/n with extended range
- 3.75G modem Pentaband Worldwide (Geo 3G model only)
- Frequencies: HSPA+/UMTS: 800/850/900/1800/1900/2100 MHz (Supports micro-SIM card only)



 Data communication interface, SMS

CAMERA (GEO MODELS):

 5MP resolution with autofocus and LED Illuminator + video capture

GPS/GNSS (GEO MODELS):

- 2 to 5 meter typical accuracy with postprocessing capability for better accuracy
- Enhanced performance under heavy canopy
- GPS, GLONASS, GALILEO, COMPASS, SBAS L1
- Integrated real-time SBAS receiver (WAAS, EGNOS, etc.)
- 32 GNSS tracking channels

CERTIFICATIONS AND STANDARDS

- FCC Class B
- CE Marking (applicable EMC, R&TTE, and LVD directives)
- Industry Canada
- EN60950 Safety
- RoHS Compliant

STANDARD ACCESSORIES

- 10600mAh battery
- AC wall charger with international plug kit
- Micro USB client sync cable
- · Quick Start Guide
- Ultra-wide hand strap
- Shipping box
- Screwdriver

